

Vehicle modeling

SIDRA Summer School,
Bertinoro 2023

Paolo Falcone

Department of Electrical Engineering,
Chalmers University of Technology,
Gothenburg, Sweden



CHALMERS



UNIMORE

Dipartimento di Ingegneria "Enzo Ferrari",
Università di Modena e Reggio Emilia,
Modena

Lecture objectives

- Lateral and longitudinal vehicle modeling

Lecture objectives

- Lateral and longitudinal vehicle modeling
- Kinematic and dynamic models

Lecture objectives


- Lateral and longitudinal vehicle modeling
- Kinematic and dynamic models
- Formulation of control and simulation oriented models

Lecture objectives

- Lateral and longitudinal vehicle modeling
- Kinematic and dynamic models
- Formulation of control and simulation oriented models
- Analysis of the basic properties of the vehicle models

Kinematic model of the lateral motion

Objective. Calculating the position variables from the speed variables, without considering the forces generating them.




Kinematic model of the lateral motion

Objective. Calculating the position variables from the speed variables, *without considering the forces generating them.*

Assumptions

- 1 The two wheels at each axle lumped into a single wheel




Kinematic model of the lateral motion

Objective. Calculating the position variables from the speed variables, *without considering the forces generating them.*

Assumptions

- 1 The two wheels at each axle lumped into a single wheel
- 2 Front and rear steered wheels




Kinematic model of the lateral motion

Objective. Calculating the position variables from the speed variables, without considering the forces generating them.

Assumptions

- 1 The two wheels at each axle lumped into a single wheel
- 2 Front and rear steered wheels
- 3 Planar motion




Kinematic model of the lateral motion

Objective. Calculating the position variables from the speed variables, *without considering the forces generating them.*

Assumptions

- 1 The two wheels at each axle lumped into a single wheel
- 2 Front and rear steered wheels
- 3 Planar motion
- 4 Wheel velocity vectors aligned with wheels directions (zero slip angles)




Kinematic model of the lateral motion

Objective. Calculating the position variables from the speed variables, *without considering the forces generating them.*

Assumptions

- 1 The two wheels at each axle lumped into a single wheel
- 2 Front and rear steered wheels
- 3 Planar motion
- 4 Wheel velocity vectors aligned with wheels directions (zero slip angles)



Notation


- 1 δ_f, δ_r steering angles,

Kinematic model of the lateral motion

Objective. Calculating the position variables from the speed variables, without considering the forces generating them.

Assumptions

- 1 The two wheels at each axle lumped into a single wheel
- 2 Front and rear steered wheels
- 3 Planar motion
- 4 Wheel velocity vectors aligned with wheels directions (zero slip angles)



Notation


- 1 δ_f, δ_r steering angles,
- 2 l_f, l_r distances of CoG from axles,

Kinematic model of the lateral motion

Objective. Calculating the position variables from the speed variables, without considering the forces generating them.

Assumptions

- 1 The two wheels at each axle lumped into a single wheel
- 2 Front and rear steered wheels
- 3 Planar motion
- 4 Wheel velocity vectors aligned with wheels directions (zero slip angles)



Notation


- 1 δ_f, δ_r steering angles,
- 2 l_f, l_r distances of CoG from axles,
- 3 X, Y, ψ longitudinal, lateral positions, heading in a global frame,

Kinematic model of the lateral motion

Objective. Calculating the position variables from the speed variables, *without considering the forces generating them.*

Assumptions

- 1 The two wheels at each axle lumped into a single wheel
- 2 Front and rear steered wheels
- 3 Planar motion
- 4 Wheel velocity vectors aligned with wheels directions (zero slip angles)



Notation


- 1 δ_f, δ_r steering angles,
- 2 l_f, l_r distances of CoG from axles,
- 3 X, Y, ψ longitudinal, lateral positions, heading in a global frame,
- 4 β vehicle slip angle,

Kinematic model of the lateral motion

Objective. Calculating the position variables from the speed variables, without considering the forces generating them.

Assumptions

- 1 The two wheels at each axle lumped into a single wheel
- 2 Front and rear steered wheels
- 3 Planar motion
- 4 Wheel velocity vectors aligned with wheels directions (zero slip angles)



Notation

- 1 δ_f, δ_r steering angles,
- 2 l_f, l_r distances of CoG from axles,
- 3 X, Y, ψ longitudinal, lateral positions, heading in a global frame,
- 4 δ steering angle,
- 5 β vehicle slip angle,
- 6 V vehicle velocity.

Kinematic model of the lateral motion

Remark about the assumption of zero slip angle.

Kinematic model of the lateral motion

Remark about the assumption of zero slip angle.

Sideways slipping (non-zero slip angle) occurs at high lateral forces (higher than tire forces) $\frac{mV^2}{R}$

Kinematic model of the lateral motion

Remark about the assumption of zero slip angle.

Sideways slipping (non-zero slip angle) occurs at high lateral forces (higher than tire forces) $\frac{mV^2}{R}$

Hence, assuming zero slip angle is legit at low vehicle speed (e.g., urban driving).

Kinematic model of the lateral motion

Remark about the assumption of zero slip angle.

Sideways slipping (non-zero slip angle) occurs at high lateral forces (higher than tire forces) $\frac{mV^2}{R}$

Hence, assuming zero slip angle is legit at low vehicle speed (e.g., urban driving).

The vehicle motion is described by the following ODEs system

$$\begin{aligned}\dot{X} &= V \cos(\psi + \beta), \\ \dot{Y} &= V \sin(\psi + \beta), \\ \dot{\psi} &= \frac{V \cos \beta}{l_f + l_r} (\tan \delta_f - \tan \delta_r), \\ \beta &= \tan^{-1} \left(\frac{l_f \tan \delta_r + l_r \tan \delta_f}{l_f + l_r} \right).\end{aligned}$$

Kinematic model of the lateral motion

Remark about the assumption of zero slip angle.

Sideways slipping (non-zero slip angle) occurs at high lateral forces (higher than tire forces) $\frac{mV^2}{R}$

Hence, assuming zero slip angle is legit at low vehicle speed (e.g., urban driving).

The vehicle motion is described by the following ODEs system

$$\begin{aligned}\dot{X} &= V \cos(\psi + \beta), \\ \dot{Y} &= V \sin(\psi + \beta), \\ \dot{\psi} &= \frac{V \cos \beta}{l_f + l_r} (\tan \delta_f - \tan \delta_r), \\ \beta &= \tan^{-1} \left(\frac{l_f \tan \delta_r + l_r \tan \delta_f}{l_f + l_r} \right).\end{aligned}$$

A nonlinear model in the state space

$$\dot{x} = f(x, u),$$


can be obtained by setting

$$x = \begin{bmatrix} X \\ Y \\ \psi \end{bmatrix}, \quad u = \begin{bmatrix} V \\ \delta_f \\ \delta_r \end{bmatrix}$$

Lateral vehicle dynamics

Write the Newton's law along the y axis

$$m\ddot{y} = - \underbrace{V_x \dot{\psi}}_{\text{centripetal acceleration}} + F_{yf} + F_{yr}.$$




Lateral vehicle dynamics

Write the Newton's law along the y axis

$$m\ddot{y} = - \underbrace{V_x \dot{\psi}}_{\text{centripetal acceleration}} + F_{yf} + F_{yr}.$$

Moment balance about the z -axis

$$I_z \ddot{\psi} = l_f F_{yf} - l_r F_{yr}.$$



Lateral vehicle dynamics

Write the Newton's law along the y axis


$$m\ddot{y} = - \underbrace{V_x \dot{\psi}}_{\text{centripetal acceleration}} + F_{yf} + F_{yr}.$$

Moment balance about the z -axis

$$I_z \ddot{\psi} = l_f F_{yf} - l_r F_{yr}.$$

Write the lateral tire forces as

$$\begin{aligned} F_{yf} &= 2C_{\alpha f}(\delta - \theta_{Vf}), \\ F_{yr} &= -2C_{\alpha r}\theta_{Vr}, \end{aligned}$$



Lateral vehicle dynamics

Write the Newton's law along the y axis

$$m\dot{y} = - \underbrace{V_x \dot{\psi}}_{\text{centripetal acceleration}} + F_{yf} + F_{yr}.$$

Moment balance about the z -axis



$$I_z \ddot{\psi} = l_f F_{yf} - l_r F_{yr}.$$

Write the lateral tire forces as

$$\begin{aligned} F_{yf} &= 2C_{af}(\delta - \theta_{Vf}), \\ F_{yr} &= -2C_{ar}\theta_{Vr}, \end{aligned}$$

where (small) tire slip angles can be approximated as

$$\theta_{Vf} = \frac{\dot{y} + l_f \dot{\psi}}{V_x}, \quad \theta_{Vr} = \frac{\dot{y} - l_r \dot{\psi}}{V_x}.$$



Lateral vehicle dynamics

The resulting, speed (V_x) dependent state space model is

$$\begin{bmatrix} \ddot{y} \\ \ddot{\psi} \\ \ddot{\psi} \end{bmatrix} = \begin{bmatrix} 0 & -\frac{2C_{af}+2C_{ar}}{mV_x} & 0 & -V_x - \frac{2C_{af}l_f-2C_{ar}l_r}{mV_x} \\ 0 & 0 & 0 & 1 \\ 0 & -\frac{2C_{af}l_f-2C_{ar}l_r}{I_zV_x} & 0 & -\frac{2C_{af}l_f^2+2C_{ar}l_r^2}{I_zV_x} \end{bmatrix} \begin{bmatrix} \dot{y} \\ \dot{\psi} \\ \dot{\psi} \end{bmatrix} + \begin{bmatrix} \frac{2C_{af}}{m} \\ 0 \\ \frac{2l_fC_{af}}{I_z} \end{bmatrix} \delta$$

Lateral vehicle dynamics

The resulting, speed (V_x) dependent state space model is

$$\begin{bmatrix} \ddot{y} \\ \ddot{\psi} \\ \ddot{\dot{\psi}} \end{bmatrix} = \begin{bmatrix} 0 & -\frac{2C_{af}+2C_{ar}}{mV_x} & 0 & -V_x - \frac{2C_{af}l_f-2C_{ar}l_r}{mV_x} \\ 0 & 0 & 0 & 1 \\ 0 & -\frac{2C_{af}l_f-2C_{ar}l_r}{I_zV_x} & 0 & -\frac{2C_{af}l_f^2+2C_{ar}l_r^2}{I_zV_x} \end{bmatrix} \begin{bmatrix} \dot{y} \\ \dot{\psi} \\ \dot{\psi} \end{bmatrix} + \begin{bmatrix} \frac{2C_{af}}{m} \\ 0 \\ \frac{2l_fC_{af}}{I_z} \end{bmatrix} \delta$$

By setting $x = \begin{bmatrix} \dot{y} \\ \dot{\psi} \\ \dot{\psi} \end{bmatrix}$, $u = \delta$,

Lateral vehicle dynamics

The resulting, speed (V_x) dependent state space model is

$$\begin{bmatrix} \ddot{y} \\ \ddot{\psi} \\ \ddot{\dot{\psi}} \end{bmatrix} = \begin{bmatrix} 0 & -\frac{2C_{af}+2C_{ar}}{mV_x} & 0 & -V_x - \frac{2C_{af}l_f-2C_{ar}l_r}{mV_x} \\ 0 & 0 & 0 & 1 \\ 0 & -\frac{2C_{af}l_f-2C_{ar}l_r}{I_zV_x} & 0 & -\frac{2C_{af}l_f^2+2C_{ar}l_r^2}{I_zV_x} \end{bmatrix} \begin{bmatrix} \dot{y} \\ \dot{\psi} \\ \dot{\dot{\psi}} \end{bmatrix} + \begin{bmatrix} \frac{2C_{af}}{m} \\ 0 \\ \frac{2l_fC_{af}}{I_z} \end{bmatrix} \delta$$

By setting $x = \begin{bmatrix} \dot{y} \\ \dot{\psi} \\ \dot{\dot{\psi}} \end{bmatrix}$, $u = \delta$, the model can be compactly rewritten as

$$\dot{x} = A(V_x)x + B(V_x)u.$$

Lateral vehicle dynamics

The resulting, speed (V_x) dependent state space model is

$$\begin{bmatrix} \ddot{y} \\ \ddot{\psi} \\ \ddot{\dot{\psi}} \end{bmatrix} = \begin{bmatrix} 0 & -\frac{2C_{af}+2C_{ar}}{mV_x} & 0 & -V_x - \frac{2C_{af}l_f-2C_{ar}l_r}{mV_x} \\ 0 & 0 & 0 & 1 \\ 0 & -\frac{2C_{af}l_f-2C_{ar}l_r}{I_zV_x} & 0 & -\frac{2C_{af}l_f^2+2C_{ar}l_r^2}{I_zV_x} \end{bmatrix} \begin{bmatrix} \dot{y} \\ \dot{\psi} \\ \dot{\dot{\psi}} \end{bmatrix} + \begin{bmatrix} \frac{2C_{af}}{m} \\ 0 \\ \frac{2l_fC_{af}}{I_z} \end{bmatrix} \delta$$

By setting $x = \begin{bmatrix} \dot{y} \\ \dot{\psi} \\ \dot{\dot{\psi}} \end{bmatrix}$, $u = \delta$, the model can be compactly rewritten as

$$\dot{x} = A(V_x)x + B(V_x)u.$$

Remark. The model has been derived under the assumption of linear tire forces. This assumption holds for small tire slip angles. More accurate tire forces reveals tire force saturations for large slip angles.

Lateral vehicle dynamics with road-aligned reference frame

Assume to know the road geometry (curvature radius).

Lateral vehicle dynamics with road-aligned reference frame

Assume to know the road geometry (curvature radius). In this case the rate of change of the desired vehicle orientation while traveling at the speed V_x is

$$\dot{\psi} = \frac{V_x}{R}.$$

Lateral vehicle dynamics with road-aligned reference frame

Assume to know the road geometry (curvature radius). In this case the rate of change of the desired vehicle orientation while traveling at the speed V_x is

$$\dot{\psi} = \frac{V_x}{R}.$$

The resulting desired acceleration is $\frac{V_x^2}{R} = V_x \dot{\psi}_{des}$.

Lateral vehicle dynamics with road-aligned reference frame

Assume to know the road geometry (curvature radius). In this case the rate of change of the desired vehicle orientation while traveling at the speed V_x is

$$\dot{\psi} = \frac{V_x}{R}.$$

The resulting desired acceleration is $\frac{V_x^2}{R} = V_x \dot{\psi}_{des}$.

By introducing

Lateral vehicle dynamics with road-aligned reference frame

Assume to know the road geometry (curvature radius). In this case the rate of change of the desired vehicle orientation while traveling at the speed V_x is

$$\dot{\psi} = \frac{V_x}{R}.$$

The resulting desired acceleration is $\frac{V_x^2}{R} = V_x \dot{\psi}_{des}$.

By introducing

- e_1 lateral deviation fo the vehicle CoG from the lane centerline (or path),

Lateral vehicle dynamics with road-aligned reference frame

Assume to know the road geometry (curvature radius). In this case the rate of change of the desired vehicle orientation while traveling at the speed V_x is

$$\dot{\psi} = \frac{V_x}{R}.$$

The resulting desired acceleration is $\frac{V_x^2}{R} = V_x \dot{\psi}_{des}$.

By introducing

- 1 e_1 lateral deviation fo the vehicle CoG from the lane centerline (or path),
- 2 e_2 orientation error w.r.t. to the road (desired path),

Lateral vehicle dynamics with road-aligned reference frame

Assume to know the road geometry (curvature radius). In this case the rate of change of the desired vehicle orientation while traveling at the speed V_x is

$$\dot{\psi} = \frac{V_x}{R}.$$

The resulting desired acceleration is $\frac{V_x^2}{R} = V_x \dot{\psi}_{des}$.

By introducing

- 1 e_1 lateral deviation for the vehicle CoG from the lane centerline (or path),
- 2 e_2 orientation error w.r.t. to the road (desired path),

the relative lateral acceleration w.r.t. road is

$$\ddot{e}_1 = (\ddot{y} + V_x \dot{\psi}) - \frac{V_x^2}{R} = \ddot{y} + V_x \underbrace{(\dot{\psi} - \dot{\psi}_{des})}_{\dot{e}_2}.$$

Lateral vehicle dynamics with road-aligned reference frame

Assume to know the road geometry (curvature radius). In this case the rate of change of the desired vehicle orientation while traveling at the speed V_x is

$$\dot{\psi} = \frac{V_x}{R}.$$

The resulting desired acceleration is $\frac{V_x^2}{R} = V_x \dot{\psi}_{des}$.

By introducing

- 1 e_1 lateral deviation for the vehicle CoG from the lane centerline (or path),
- 2 e_2 orientation error w.r.t. to the road (desired path),

the relative lateral acceleration w.r.t. road is

$$\ddot{e}_1 = (\ddot{y} + V_x \dot{\psi}) - \underbrace{\frac{V_x^2}{R}}_{\dot{e}_2} = \ddot{y} + V_x (\dot{\psi} - \dot{\psi}_{des}).$$

By combining with the Newton's law....

Lateral vehicle dynamics with road-aligned reference frame

$$\begin{bmatrix} \dot{e}_1 \\ \ddot{e}_1 \\ \dot{e}_2 \\ \ddot{e}_2 \end{bmatrix} = \begin{bmatrix} 0 & 1 & 0 & 0 \\ 0 & -\frac{2C_{af}+2C_{ar}}{mV_x} & \frac{2C_{af}+2C_{ar}}{m} & \frac{-2C_{af}l_f-2C_{ar}l_r}{mV_x} \\ 0 & 0 & 0 & 1 \\ 0 & -\frac{2C_{af}l_f-2C_{ar}l_r}{I_zV_x} & \frac{2C_{af}l_f-2C_{ar}l_r}{I_z} & -\frac{2C_{af}l_f^2+2C_{ar}l_r^2}{I_zV_x} \end{bmatrix} \begin{bmatrix} e_1 \\ \dot{e}_1 \\ e_2 \\ \dot{e}_2 \end{bmatrix} + \begin{bmatrix} 0 \\ \frac{2C_{af}}{m} \\ 0 \\ \frac{2l_fC_{af}}{I_z} \end{bmatrix} \delta \\
 + \begin{bmatrix} 0 \\ -\frac{2C_{af}l_f-2C_{ar}l_r}{mV_x} - V_x \\ 0 \\ -\frac{2C_{af}l_f^2+2C_{ar}l_r^2}{I_zV_x} \end{bmatrix} \dot{\psi}_{des}$$

Lateral vehicle dynamics with road-aligned reference frame

$$\begin{bmatrix} \dot{e}_1 \\ \ddot{e}_1 \\ \dot{e}_2 \\ \ddot{e}_2 \end{bmatrix} = \begin{bmatrix} 0 & 1 & 0 & 0 \\ 0 & -\frac{2C_{af}+2C_{ar}}{mV_x} & \frac{2C_{af}+2C_{ar}}{m} & \frac{-2C_{af}l_f-2C_{ar}l_r}{mV_x} \\ 0 & 0 & 0 & 1 \\ 0 & -\frac{2C_{af}l_f-2C_{ar}l_r}{I_zV_x} & \frac{2C_{af}l_f-2C_{ar}l_r}{I_z} & -\frac{2C_{af}l_f^2+2C_{ar}l_r^2}{I_zV_x} \end{bmatrix} \begin{bmatrix} e_1 \\ \dot{e}_1 \\ e_2 \\ \dot{e}_2 \end{bmatrix} + \begin{bmatrix} 0 \\ \frac{2C_{af}}{m} \\ 0 \\ \frac{2l_fC_{af}}{I_z} \end{bmatrix} \delta$$

$$+ \begin{bmatrix} 0 \\ -\frac{2C_{af}l_f-2C_{ar}l_r}{mV_x} - V_x \\ 0 \\ -\frac{2C_{af}l_f^2+2C_{ar}l_r^2}{I_zV_x} \end{bmatrix} \dot{\psi}_{des}$$

By setting $x = \begin{bmatrix} e_1 \\ \dot{e}_1 \\ e_2 \\ \dot{e}_2 \end{bmatrix}$, $u = \delta$, $d = \dot{\psi}_{des}$

Lateral vehicle dynamics with road-aligned reference frame

$$\begin{bmatrix} \dot{e}_1 \\ \ddot{e}_1 \\ \dot{e}_2 \\ \ddot{e}_2 \end{bmatrix} = \begin{bmatrix} 0 & 1 & 0 & 0 \\ 0 & -\frac{2C_{af}+2C_{ar}}{mV_x} & \frac{2C_{af}+2C_{ar}}{m} & \frac{-2C_{af}l_f-2C_{ar}l_r}{mV_x} \\ 0 & 0 & 0 & 1 \\ 0 & -\frac{2C_{af}l_f-2C_{ar}l_r}{I_zV_x} & \frac{2C_{af}l_f-2C_{ar}l_r}{I_z} & -\frac{2C_{af}l_f^2+2C_{ar}l_r^2}{I_zV_x} \end{bmatrix} \begin{bmatrix} e_1 \\ \dot{e}_1 \\ e_2 \\ \dot{e}_2 \end{bmatrix} + \begin{bmatrix} 0 \\ \frac{2C_{af}}{m} \\ 0 \\ \frac{2l_fC_{af}}{I_z} \end{bmatrix} \delta$$


$$+ \begin{bmatrix} 0 \\ -\frac{2C_{af}l_f-2C_{ar}l_r}{mV_x} - V_x \\ 0 \\ -\frac{2C_{af}l_f^2+2C_{ar}l_r^2}{I_zV_x} \end{bmatrix} \dot{\psi}_{des}$$

By setting $x = \begin{bmatrix} e_1 \\ \dot{e}_1 \\ e_2 \\ \dot{e}_2 \end{bmatrix}$, $u = \delta$, $d = \dot{\psi}_{des}$ the model can be compactly rewritten as

$$\dot{x} = A(V_x)x + B(V_x)u + B_d(V_x)d.$$

Transformation into global coordinates

Objective. Calculating the global coordinates X, Y from e_1, e_2 .




Transformation into global coordinates

Objective. Calculating the global coordinates X , Y from e_1 , e_2 .

The global coordinates are calculated from the coordinates of the desired path and the lateral deviation e_1

$$X = X_{des} - e_1 \sin \psi_{des}$$

$$Y = Y_{des} + e_1 \cos \psi_{des}$$



Transformation into global coordinates

Objective. Calculating the global coordinates X , Y from e_1 , e_2 .

The global coordinates are calculated from the coordinates of the desired path and the lateral deviation e_1

$$X = X_{des} - e_1 \sin \psi_{des}$$


$$Y = Y_{des} + e_1 \cos \psi_{des}$$

Using

$$X_{des} = \int_0^t V \cos \psi_{des} dt,$$

$$Y_{des} = \int_0^t V \sin \psi_{des} dt,$$

$$\psi = e_2 + \psi_{des}$$



Transformation into global coordinates

Objective. Calculating the global coordinates X, Y from e_1, e_2 .

The global coordinates are calculated from the coordinates of the desired path and the lateral deviation e_1

$$X = X_{des} - e_1 \sin \psi_{des},$$


$$Y = Y_{des} + e_1 \cos \psi_{des}$$

Using

$$X_{des} = \int_0^t V \cos \psi_{des} dt,$$

$$Y_{des} = \int_0^t V \sin \psi_{des} dt,$$

$$\psi = e_2 + \psi_{des}$$




the global coordinates are written as

$$X = \int_0^t V \cos \psi_{des} dt - e_1 \sin(e_2 + \psi_{des}),$$

$$Y = \int_0^t V \sin \psi_{des} dt + e_1 \cos(e_2 + \psi_{des}).$$


Longitudinal vehicle dynamics



Longitudinal vehicle dynamics

Notation


- 1 F_{xf} , F_{xr} front and rear longitudinal tire forces,



Longitudinal vehicle dynamics

Notation


- 1 F_{xf} , F_{xr} front and rear longitudinal tire forces,
- 2 F_{aero} air drag force,



Longitudinal vehicle dynamics

Notation


- 1 F_{xf} , F_{xr} front and rear longitudinal tire forces,
- 2 F_{aero} air drag force,
- 3 R_{xf} , R_{xr} rolling resistance forces,



Longitudinal vehicle dynamics

Notation


- 1 F_{xf} , F_{xr} front and rear longitudinal tire forces,
- 2 F_{aero} air drag force,
- 3 R_{xf} , R_{xr} rolling resistance forces,
- 4 m vehicle mass,



Longitudinal vehicle dynamics

Notation


- 1 F_{xf} , F_{xr} front and rear longitudinal tire forces,
- 2 F_{aero} air drag force,
- 3 R_{xf} , R_{xr} rolling resistance forces,
- 4 m vehicle mass,
- 5 g gravitational acceleration,



Longitudinal vehicle dynamics

Notation


- 1 F_{xf}, F_{xr} front and rear longitudinal tire forces,
- 2 F_{aero} air drag force,
- 3 R_{xf}, R_{xr} rolling resistance forces,
- 4 m vehicle mass,
- 5 g gravitational acceleration,
- 6 θ road grade.



Longitudinal vehicle dynamics

Notation

- 1 F_{xf} , F_{xr} front and rear longitudinal tire forces,
- 2 F_{aero} air drag force,
- 3 R_{xf} , R_{xr} rolling resistance forces,
- 4 m vehicle mass,
- 5 g gravitational acceleration,
- 6 θ road grade.




Write the Newton's law along the vehicle longitudinal axis

$$m\ddot{x} = F_{xf} + F_{xr} - F_{aero} - R_{xf} - R_{xr} - mg \sin \theta.$$

Longitudinal vehicle dynamics

Notation

- 1 F_{xf}, F_{xr} front and rear longitudinal tire forces,
- 2 F_{aero} air drag force,
- 3 R_{xf}, R_{xr} rolling resistance forces,
- 4 m vehicle mass,
- 5 g gravitational acceleration,
- 6 θ road grade.



Write the Newton's law along the vehicle longitudinal axis

$$m\ddot{x} = F_{xf} + F_{xr} - F_{aero} - R_{xf} - R_{xr} - mg \sin \theta.$$

Air drag force

$$F_{aero} = \frac{1}{2} \rho C_d A_F (V_x + V_{wind})^2,$$


$$A_F = 1.6 + 0.00056(m - 765),$$

$$m \in [800 - 2000]Kg$$

Longitudinal vehicle dynamics

Notation

- 1 F_{xf}, F_{xr} front and rear longitudinal tire forces,
- 2 F_{aero} air drag force,
- 3 R_{xf}, R_{xr} rolling resistance forces,
- 4 m vehicle mass,
- 5 g gravitational acceleration,
- 6 θ road grade.



Write the Newton's law along the vehicle longitudinal axis

$$m\ddot{x} = F_{xf} + F_{xr} - F_{aero} - R_{xf} - R_{xr} - mg \sin \theta.$$

Air drag force



$$F_{aero} = \frac{1}{2} \rho C_d A_F (V_x + V_{wind})^2,$$
$$A_F = 1.6 + 0.00056(m - 765),$$
$$m \in [800 - 2000] \text{Kg}$$

Longitudinal tire forces

$$F_{x\star} = C_{\sigma\star} \sigma_{x\star},$$
$$\sigma_{x\star} = \frac{r_w \omega_{w\star} - V_x}{r_w \omega_{w\star}}, \quad \star \in \{f, r\}$$



Tire forces

The interaction between the tire contact patch and the road generates a number of forces and moments



Tire forces

The interaction between the tire contact patch and the road generates a number of forces and moments



In this course we are interested in modeling the forces F_x , F_y , as function of the vehicle states and control input.

$$F_{x\star} = f_x(\alpha_\star, \sigma_\star, \mu_\star, F_{z\star}),$$

$$F_{y\star} = f_y(\alpha_\star, \sigma_\star, \mu_\star, F_{z\star}).$$

Tire forces

Longitudinal tire forces

$$F_{x\star} = C_{\sigma\star} \sigma_{x\star},$$


$$\sigma_{x\star} = \frac{r_w \omega_{w\star} - V_x}{r_w \omega_{w\star}}, \quad \star \in \{f, r\}$$

Tire forces

Longitudinal tire forces

$$F_{x\star} = C_{\sigma\star} \sigma_{x\star},$$

$$\sigma_{x\star} = \frac{r_w \omega_{w\star} - V_x}{r_w \omega_{w\star}}, \quad \star \in \{f, r\}$$




The forces have been plotted for a constant normal force F_z and varying friction coefficient μ .

Tire forces

Longitudinal tire forces

$$F_{x\star} = C_{\sigma\star} \sigma_{x\star},$$

$$\sigma_{x\star} = \frac{r_w \omega_{w\star} - V_x}{r_w \omega_{w\star}}, \quad \star \in \{f, r\}$$



The forces have been plotted for a constant normal force F_z and varying friction coefficient μ .


These are *static* tire forces characteristics. Indeed, tire dynamics are fast and can be neglected in our applications.

Tire forces

Longitudinal tire forces

$$F_{x\star} = C_{\sigma\star} \sigma_{x\star},$$

$$\sigma_{x\star} = \frac{r_w \omega_{w\star} - V_x}{r_w \omega_{w\star}}, \quad \star \in \{f, r\}$$



The forces have been plotted for a constant normal force F_z and varying friction coefficient μ .

These are *static* tire forces characteristics. Indeed, tire dynamics are fast and can be neglected in our applications.

Lateral tire forces

$$F_{y\star} = C_{\alpha\star} \alpha_{\star},$$


$$\alpha_f = \delta - \theta_{Vf}, \quad \alpha_r = -\theta_{Vr}.$$

Tire forces

Longitudinal tire forces

$$F_{x\star} = C_{\sigma\star} \sigma_{x\star},$$

$$\sigma_{x\star} = \frac{r_w \omega_{w\star} - V_x}{r_w \omega_{w\star}}, \quad \star \in \{f, r\}$$




The forces have been plotted for a constant normal force F_z and varying friction coefficient μ .

These are *static* tire forces characteristics. Indeed, tire dynamics are fast and can be neglected in our applications.

Lateral tire forces

$$F_{y\star} = C_{\alpha\star} \alpha_{\star},$$

$$\alpha_f = \delta - \theta_{Vf}, \quad \alpha_r = -\theta_{Vr}.$$



Tire forces



The characteristics seen so far show the tire forces in *pure braking/driving and cornering*.

Tire forces

The characteristics seen so far show the tire forces in *pure braking/driving and cornering*. In combined braking/driving and cornering manoeuvres,



Tire forces

The characteristics seen so far show the tire forces in *pure braking/driving and cornering*. In combined braking/driving and cornering manoeuvres,



Tire forces

The characteristics seen so far show the tire forces in *pure braking/driving and cornering*. In combined braking/driving and cornering manoeuvres,



Physical modeling of the tire forces can be very much involving.

Although useful physical tire models exist (Brush model, LuGre friction model, Dugoff's model), the *semi-empirical Pacejka's model* is the most widespread.

The magic formula

The Pacejka's tire model relies on functions, which are "shaped" to resemble the tire forces.


$$Y(X) = D \sin (C \arctan (B\Phi(X))) + S_v$$

The magic formula

The Pacejka's tire model relies on functions, which are "shaped" to resemble the tire forces.

$$Y(X) = D \sin(C \arctan(B\Phi(X))) + S_v$$

- Y is either the longitudinal or lateral generated force,




The magic formula

The Pacejka's tire model relies on functions, which are "shaped" to resemble the tire forces.

$$Y(X) = D \sin (C \arctan (B\Phi(X))) + S_v$$

- Y is either the longitudinal or lateral generated force,
- X is either the slip ratio or the tire slip angle,




The magic formula

The Pacejka's tire model relies on functions, which are "shaped" to resemble the tire forces.

$$Y(X) = D \sin (C \arctan (B\Phi(X))) + S_v$$

- Y is either the longitudinal or lateral generated force,
- X is either the slip ratio or the tire slip angle,
- D is the *peak factor*,




The magic formula

The Pacejka's tire model relies on functions, which are “shaped” to resemble the tire forces.

$$Y(X) = D \sin (C \arctan (B\Phi(X))) + S_v$$

- Y is either the longitudinal or lateral generated force,
- X is either the slip ratio or the tire slip angle,
- D is the *peak factor*,
- C is the *shape factor*,




The magic formula

The Pacejka's tire model relies on functions, which are “shaped” to resemble the tire forces.

$$Y(X) = D \sin (C \arctan (B\Phi(X))) + S_v$$

- Y is either the longitudinal or lateral generated force,
- X is either the slip ratio or the tire slip angle,
- D is the *peak factor*,
- C is the *shape factor*,
- B is the *stiffness factor*,




The magic formula

The Pacejka's tire model relies on functions, which are “shaped” to resemble the tire forces.

$$Y(X) = D \sin (C \arctan (B\Phi(X))) + S_v$$

- Y is either the longitudinal or lateral generated force,
- X is either the slip ratio or the tire slip angle,
- D is the *peak factor*,
- C is the *shape factor*,
- B is the *stiffness factor*,
- S_v is the *vertical shift*,



The magic formula

The Pacejka's tire model relies on functions, which are "shaped" to resemble the tire forces.


$$Y(X) = D \sin (C \arctan (B\Phi(X))) + S_v$$

- Y is either the longitudinal or lateral generated force,
- X is either the slip ratio or the tire slip angle,
- D is the *peak factor*,
- C is the *shape factor*,
- B is the *stiffness factor*,

- Φ is defined as:

$$\Phi(X) = (1 - E) (X + S_h) + (E/B) \arctan (B(X + S_h)),$$

where E is the *curvature factor* and S_h is the *horizontal shift*



The magic formula

The Pacejka's tire model relies on functions, which are "shaped" to resemble the tire forces.


$$Y(X) = D \sin (C \arctan (B\Phi(X))) + S_v$$

- Y is either the longitudinal or lateral generated force,
- X is either the slip ratio or the tire slip angle,
- D is the *peak factor*,
- C is the *shape factor*,
- B is the *stiffness factor*,
- Φ is defined as:

$$\Phi(X) = (1 - E) (X + S_h) + (E/B) \arctan (B(X + S_h)),$$

where E is the *curvature factor* and S_h is the *horizontal shift*

The parameters in the magic formula are calibrated on experimental data.



Longitudinal tire forces and wheels dynamics

In order to calculate F_x we need the tire longitudinal slip. This depends on the wheels speed.

$$m\ddot{x} = F_{xf} + F_{xr} - F_{aero} - R_{xf} - R_{xr} - mg \sin \theta,$$

Longitudinal tire forces and wheels dynamics

In order to calculate F_x we need the tire longitudinal slip. This depends on the wheels speed.

$$m\ddot{x} = F_{xf} + F_{xr} - F_{aero} - R_{xf} - R_{xr} - mg \sin \theta,$$

$$F_{x\star} = f_x(\alpha_{\star}, \sigma_{\star}, \mu_{\star}, F_{z\star}),$$

Longitudinal tire forces and wheels dynamics

In order to calculate F_x we need the tire longitudinal slip. This depends on the wheels speed.

$$m\ddot{x} = F_{xf} + F_{xr} - F_{aero} - R_{xf} - R_{xr} - mg \sin \theta,$$
$$F_{x\star} = f_x(\alpha_{\star}, \sigma_{\star}, \mu_{\star}, F_{z\star}),$$
$$\sigma_{\star} = \begin{cases} \frac{r_w \omega_{\star}}{V_{x\star}} - 1 & \text{if } V_{x\star} > r_w \omega_{\star}, V_{x\star} \neq 0 \text{ for braking} \\ 1 - \frac{v_{x\star}}{r_w \omega_{\star}} & \text{if } V_{x\star} < r_w \omega_{\star}, \omega_{\star} \neq 0 \text{ for driving,} \end{cases}$$

Longitudinal tire forces and wheels dynamics

In order to calculate F_x we need the tire longitudinal slip. This depends on the wheels speed.

$$m\ddot{x} = F_{xf} + F_{xr} - F_{aero} - R_{xf} - R_{xr} - mg \sin \theta,$$

$$F_{x\star} = f_x(\alpha_{\star}, \sigma_{\star}, \mu_{\star}, F_{z\star}),$$

$$\sigma_{\star} = \begin{cases} \frac{r_w \omega_{\star}}{V_{x\star}} - 1 & \text{if } V_{x\star} > r_w \omega_{\star}, V_{x\star} \neq 0 \text{ for braking} \\ 1 - \frac{v_{x\star}}{r_w \omega_{\star}} & \text{if } V_{x\star} < r_w \omega_{\star}, \omega_{\star} \neq 0 \text{ for driving,} \end{cases}$$

$$J_{w,\star} \dot{\omega}_{\star,\bullet} = -F_{l_{\star,\bullet}} r_w - b \cdot \omega_{\star,\bullet} - T_{b_{\star,\bullet}} + T_{t_{\star,\bullet}},$$

$$\star \in \{f, r\}, \bullet \in \{l, r\}$$

Longitudinal tire forces and wheels dynamics

In order to calculate F_x we need the tire longitudinal slip. This depends on the wheels speed.

$$m\ddot{x} = F_{xf} + F_{xr} - F_{aero} - R_{xf} - R_{xr} - mg \sin \theta,$$

$$F_{x\star} = f_x(\alpha_{\star}, \sigma_{\star}, \mu_{\star}, F_{z\star}),$$

$$\sigma_{\star} = \begin{cases} \frac{r_w \omega_{\star}}{V_{x\star}} - 1 & \text{if } V_{x\star} > r_w \omega_{\star}, V_{x\star} \neq 0 \text{ for braking} \\ 1 - \frac{v_{x\star}}{r_w \omega_{\star}} & \text{if } V_{x\star} < r_w \omega_{\star}, \omega_{\star} \neq 0 \text{ for driving,} \end{cases}$$

$$J_{w,\star} \dot{\omega}_{\star,\bullet} = -F_{l_{\star,\bullet}} r_w - b \cdot \omega_{\star,\bullet} - T_{b_{\star,\bullet}} + T_{t_{\star,\bullet}},$$

$$\star \in \{f, r\}, \bullet \in \{l, r\}$$

Remarks.

Longitudinal tire forces and wheels dynamics

In order to calculate F_x we need the tire longitudinal slip. This depends on the wheels speed.

$$m\ddot{x} = F_{xf} + F_{xr} - F_{aero} - R_{xf} - R_{xr} - mg \sin \theta,$$

$$F_{x\star} = f_x(\alpha_{\star}, \sigma_{\star}, \mu_{\star}, F_{z\star}),$$

$$\sigma_{\star} = \begin{cases} \frac{r_w \omega_{\star}}{V_{x\star}} - 1 & \text{if } V_{x\star} > r_w \omega_{\star}, V_{x\star} \neq 0 \text{ for braking} \\ 1 - \frac{v_{x\star}}{r_w \omega_{\star}} & \text{if } V_{x\star} < r_w \omega_{\star}, \omega_{\star} \neq 0 \text{ for driving,} \end{cases}$$

$$J_{w,\star} \dot{\omega}_{\star,\bullet} = -F_{l_{\star,\bullet}} r_w - b \cdot \omega_{\star,\bullet} - T_{b_{\star,\bullet}} + T_{t_{\star,\bullet}},$$

$$\star \in \{f, r\}, \bullet \in \{l, r\}$$

Remarks.

- $V_{x\star}$ should be the wheel velocity. You can approximate it with the vehicle speed.

Longitudinal tire forces and wheels dynamics

In order to calculate F_x we need the tire longitudinal slip. This depends on the wheels speed.

$$m\ddot{x} = F_{xf} + F_{xr} - F_{aero} - R_{xf} - R_{xr} - mg \sin \theta,$$

$$F_{x\star} = f_x(\alpha_\star, \sigma_\star, \mu_\star, F_{z\star}),$$

$$\sigma_\star = \begin{cases} \frac{r_w \omega_\star}{V_{x\star}} - 1 & \text{if } V_{x\star} > r_w \omega_\star, V_{x\star} \neq 0 \text{ for braking} \\ 1 - \frac{v_{x\star}}{r_w \omega_\star} & \text{if } V_{x\star} < r_w \omega_\star, \omega_\star \neq 0 \text{ for driving,} \end{cases}$$

$$J_{w,\star} \dot{\omega}_{\star,\bullet} = -F_{l_{\star,\bullet}} r_w - b \cdot \omega_{\star,\bullet} - T_{b_{\star,\bullet}} + T_{t_{\star,\bullet}},$$

$$\star \in \{f, r\}, \bullet \in \{l, r\}$$

Remarks.

- $V_{x\star}$ should be the wheel velocity. You can approximate it with the vehicle speed.
- F_{aero} , R_{xf} , R_{xr} , $mg \sin \theta$ can be neglected in some vehicles speed regimes and under the assumption of flat road, respectively,

Longitudinal tire forces and wheels dynamics

In order to calculate F_x we need the tire longitudinal slip. This depends on the wheels speed.

$$m\ddot{x} = F_{xf} + F_{xr} - F_{aero} - R_{xf} - R_{xr} - mg \sin \theta,$$

$$F_{x\star} = f_x(\alpha_\star, \sigma_\star, \mu_\star, F_{z\star}),$$

$$\sigma_\star = \begin{cases} \frac{r_w \omega_\star}{V_{x\star}} - 1 & \text{if } V_{x\star} > r_w \omega_\star, V_{x\star} \neq 0 \text{ for braking} \\ 1 - \frac{v_{x\star}}{r_w \omega_\star} & \text{if } V_{x\star} < r_w \omega_\star, \omega_\star \neq 0 \text{ for driving,} \end{cases}$$

$$J_{w,\star} \dot{\omega}_{\star,\bullet} = -F_{l_{\star,\bullet}} r_w - b \cdot \omega_{\star,\bullet} - T_{b_{\star,\bullet}} + T_{t_{\star,\bullet}},$$

$$\star \in \{f, r\}, \bullet \in \{l, r\}$$

Remarks.

- $V_{x\star}$ should be the wheel velocity. You can approximate it with the vehicle speed.
- F_{aero} , R_{xf} , R_{xr} , $mg \sin \theta$ can be neglected in some vehicles speed regimes and under the assumption of flat road, respectively,
- $T_{b_{\star,\bullet}}$, $T_{t_{\star,\bullet}}$ can be seen as *control inputs* to the system.